



## Speed, quality and reliability for the demanding environment

The ES9130 offers a truly efficient solution for the busiest departments and most demanding environments. With the ability to tackle heavy workloads and high volume throughput, the ES9130 will relieve printing bottlenecks and maximise printing productivity.

Speed and versatility ensure that the ES9130 meets the needs of the busiest departments. A high paper capacity of up to 5,100 A4 pages from up to 6 sources and an optional finisher offering hole punching and stapling, the ES9130 is a valuable addition to any workgroup or department.

Print speeds of 50 pages per minute (ppm) ensure that long print runs are addressed with ease and that high volume mission critical transactional print requirements are tackled with minimal fuss and intervention.

Printing resolutions of 1200 x 1200dpi ensuring exceptional quality together with unsurpassed reliability make the ES9130 the sensible choice for the intelligent user.

### Exceptional performance

- An incredibly fast print speed of 50ppm when printing A4 and 28ppm for A3
- No compromise on print quality - true 1200 x 1200dpi resolution for clear, sharp detail
- Takes just 3 seconds from a warm start to print the first page
- 600MHz controller means no delay when processing large amounts of data
- 256MB (max 768MB) memory capacity to manage with a multitude of print tasks
- Optional interface - 1GB Base TX Ethernet

### A range of utilities make things simple

- With PrintSuperVision, network administrators can remotely monitor all networked printers and verify toner status
- Secure Print encrypts files sent over the network ensuring that office critical information is kept confidential (optional Hard Disk Drive required).
- Template Manager provides easy to use templates for help in printing envelopes and address labels

### Built to perform. Maintaining productivity

- Robust design to handle heavy print workloads
- High 300,000 pages/month duty cycle to maintain productivity
- Optional paper trays extend input capacity to 5,100 sheets, for volume printing

### Extra options to extend in-house capability

- Offers various input and finishing options, including 2,000 A4 sheet High Capacity Feeder unit and Finisher unit with stapler and 2-4 hole puncher
- Optional Compact Flash™ memory for extra data storage e.g. fonts, logos.

# The ES9130 Mono Printer

		ES9130
Order number		01260001
Speed & throughput	Print speed	A4: 50ppm, A3: 28ppm
	Time to first print	3 seconds (warm start)
	Warm up time	up to 45 seconds from power on
	Processor speed	600MHz
Print quality	Resolution	1200 x 1200dpi
Typefaces	Printers fonts	99 scalable PCL fonts, 47 bitmap symbol sets & 136 PostScript fonts
	Barcode fonts	11 types of one dimension with 28 variations: UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4POSTNET
Compatibility	Printer languages	PCL6, PCL5e, PostScript 3, SIDM (Epson FX)
	Connectivity	Hi-Speed USB 2.0, IEEE1284 (ECP) parallel, RS-232C serial, 10/100BaseTX Ethernet
	Network & protocols	10/100 Base TX Ethernet on board with internal web server for printers and network set-up and management. Includes SMTP mail client for alerts. Major protocols supported: TCP/IP, Netware 5.x and 6.x, and EtherTalk. TCP/IP: ARP, IPv4, ICMP, UDP, TCP, LPR, HTTP, SMTP, BOOTP, DHCP, SNMPv1, SNMPv2, DNS, WINS, IPX/SPX, and Apple Bonjour protocols
	OS Compatibility <sup>1</sup>	Windows 2000 / XP Home / XP Professional / XP Professional x64 / Vista (32-bit) / Vista (64-bit) / Server 2003 / Server 2003 for x64; Mac OS X PowerPC 10.2 or greater / OS X Intel 10.4.4 or greater
Utility Suite <sup>2</sup>		Template Manager 3.0 <sup>2</sup> , PrintSuperVision, OKI LPR, PDF Direct Print <sup>3</sup>
Memory	RAM	Standard: 256MB; Maximum: 768MB
Paper handling	Paper capacity	Tray 1: 500 sheets of 80gsm; Tray 2: 500 sheets of 80gsm; Multi-purpose feeder: 100 sheets of 80gsm
	Paper capacity optional paper trays	Tandem-tray: 1,200 + 800 sheets of 80gsm; Two-tray: 2 x 500 sheets 80gsm; High Capacity Feeder: 2,000 sheets of 80gsm
	Paper sizes	Tray 1/2: A3, A4, A5, A6, B5, Letter, Legal 13 & 14, Executive, Statement, Custom size: Width 140 – 297mm, Length 182 – 432mm; Envelopes: Com-9, DL, C5, Monarch; Multi-purpose feeder: A3, A4, A5, A6, B5, Letter, Legal 13 & 14, Executive, Statement, Custom size: Width 89 – 297mm, Length 98.4 – 432mm; Envelopes: Com-9, DL, C5, Monarch; Duplex: A3, A4, A5, B5, Letter, Legal 13 & 14, Executive, Statement, Custom size: Width 89 - 297mm Length 127 - 432mm; Tandem-tray: A4, B5, Letter, Executive; Two-tray: A3, A4, A5, B5, Letter, Legal 13 & 14, Executive, Statement; High Capacity Feeder: A4, B5, Letter, Executive
	Paper weight	Tray 1: 60 to 105gsm; Tray 2: 60 to 215gsm; Multi-purpose feeder: 60 to 215gsm; Duplex: 60 to 163gsm; Tandem tray: 60 to 215gsm; Two-tray: 60 to 215gsm; High Capacity Feeder: 60 to 215gsm
	Duplex	Standard
	Standard paper output	500 sheets face down
Operating conditions	Temperature/Humidity	5°C to 32°C, 15% to 85% RH non-condensing
	Storage	5°C to 32°C, 5% to 85% RH non-condensing
Power requirements	Power supply	230 VAC +/- 10%, 50 or 60Hz +/- 2%
	Power consumption	Peak 1,300W, Stand-by 140W, Sleep mode 10W
Noise level		Operating: Up to 54dB(A), Standby: 22dB(A), Power Save: Background Level
Dimensions (HxWxD)		577 x 640 x 525mm
Weight <sup>4</sup>		approx 48.4kgs
Accessories	A4 Tandem-tray (2,000 sheets)	o (01222001)
	A3 Two-tray (2 x 500 sheets)	o (01221901)
	High Capacity Feeder	o (01222101)
	Finisher	o (01222301)
	Staple refill pack (15,000 staples)	o (01244301)
	1GB Network I/F kit	o (09004584)
	Memory	o 256MB (09004628), 512MB (09004629)
	Hard Disk Drive	o 60GB (09004630), 120GB (09004631)
Compact Flash	o 256MB (09004632), 512MB (09004633), 1GB (09004634)	

o Optional (order number), <sup>1</sup>Check local OKI Executive Series website for latest driver releases and OS Compatibility, <sup>2</sup>Windows only, <sup>3</sup>Hard Disk Drive required, <sup>4</sup>Includes all consumables

**Consumables Information:** For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI Printing Solutions toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

Specification subject to change without notice. All trademarks acknowledged.



OKI SYSTEMS (UK) LTD.  
550 DUNDEE ROAD, SLOUGH  
BERKSHIRE, SL1 4LE  
UNITED KINGDOM  
T +44(0) 1753 819819  
F +44(0) 1753 819899  
WWW.OKIPRINTINGSOLUTIONS.

**OKI**  
PRINTING SOLUTIONS